



according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3-D Laserscanning Entspiegelungsspray

Further trade names

Article no. (user): 119.990.001 119.990.004

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Inspection of metals

1.3. Details of the supplier of the safety data sheet

Company name: Helling GmbH
Street: Spoekerdamm 2
Place: D-25436 Heidgraben

Telephone: +49-4122-922-0 Telefax: +49-4122-922-201

e-mail: info@helling.de Internet: www.helling.de 1.4. Emergency telephone +49-4122-922-0

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: F+ - Extremely flammable, Xi - Irritant

R phrases:

Extremely flammable. Irritating to eyes.

Vapours may cause drowsiness and dizziness.

GHS classification

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Hazardous components which must be listed on the label

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms: GHS02-GHS07







according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 2 of 9

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to industrial incineration plant.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
203-448-7	butane	50 - 60 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	
200-827-9	propane	20 - 25 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1; H220	
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	10 - 20 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
200-857-2	isobutane	2 - 4 %
75-28-5	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1; H220	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).



Helling GmbH

according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 3 of 9

After contact with skin

Wash with plenty of water. Change contaminated clothing.

After contact with eves

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: Headache. drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

Flammable liquids: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition.





according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 4 of 9

- No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent

7.3. Specific end use(s)

Inspection of metals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls





Occupational exposure controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. When using do not eat or drink. After work, wash hands and face.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Recommended protective gloves brand: NR (Natural rubber (Caoutchouc), Natural latex). Protect skin by using skin protective cream.

Eye protection

Wear eye/face protection.

Skin protection

Body protection: not required.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: white
Odour: characteristic



Helling GmbH

according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 5 of 9

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined
Initial boiling point and boiling range: not determined
Flash point: not determined

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

Heating causes rise in pressure with risk of bursting. Vapours may form explosive mixtures with air.

Lower explosion limits: not determined Upper explosion limits: not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

Not oxidizing.

Vapour pressure: not determined

Density (at 20 °C): 0,925 g/cm³

Water solubility: slightly soluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: ~10%

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention.

10.2. Chemical stability

No risks worthy of mention.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Remove all sources of ignition. Keep away from heat.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide, Carbon monoxide,

SECTION 11: Toxicological information



according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 6 of 9

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
106-97-8	butane				
	inhalative (4 h) vapour	LC50	> 20 mg/l	Rat	
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS
74-98-6	propane				
	inhalative (4 h) vapour	LC50	> 20 mg/l	Rat	

Irritation and corrosivity

Irritant effect on the skin: Not an irritant. Irritant effect on the eye: Irritant.

Sensitising effects

No sensitizing effect known.

Carcinogenic/mutagenic/toxic effects for reproduction

According to current knowledge not a carcinogen. According to current knowledge not mutagen. According to current knowledge not reproduction toxic.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity: No data available

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	h	Species	Source
106-97-8	butane					
	Acute fish toxicity	LC50	> 100 mg/l	96 h		
	Acute algae toxicity	ErC50	> 100 mg/l			
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h		
74-98-6	propane					
	Acute fish toxicity	LC50	> 100 mg/l	96 h		
	Acute algae toxicity	ErC50	> 100 mg/l			
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36
75-28-5	isobutane	2,8



Helling GmbH

according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 7 of 9

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing dangerous substances Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2 Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

Inland waterways transport (ADN)

14.1. UN number: 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2 Hazard label: 2.1





according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 8 of 9



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Other applicable information (inland waterways transport)

Marine transport (IMDG)

14.1. UN number: 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

Other applicable information (marine transport)

Air transport (ICAO)

UN/ID number: 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1 Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

Passenger-LQ: Y203

E0

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information



Helling GmbH

according to Regulation (EC) No 1907/2006

3-D Laserscanning Entspiegelungsspray

Print date: 26.09.2014 Page 9 of 9

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 56 % (518 g/l)

National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

section 2

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant R-phrases (Number and full text)

11	Highly flammable.
12	Extremely flammable.
36	Irritating to eyes.

67 Vapours may cause drowsiness and dizziness.

Relevant H- and EUH-phrases (Number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)